

INSPECTION CHECKLIST HARNES

All personal fall arrest system components must be inspected prior to each use and at least annually by a competent person. If equipment does not meet inspection criteria outlined in manual and/or if subject to fall arrest forces remove from service immediately.

HARNES PART #:	COMPANY NAME:
SERIAL #:	INSPECTOR NAME:
DATE OF MANUFACTURE:	SIGNATURE:
DATE OF ACTIVATION:	DATE OF FIRST INSPECTION:

LABELS & MARKINGS	Pass	Fail	Note
1. Label (Intact & Legible)			
2. Appropriate ANSI/OSHA Markings			
3. Inspected in the last year			
4. Impact Indicator			

HARDWARE
Connectors and D-Rings must not be damaged or broken or show signs of corrosion, defects, cracks, sharp edges, burns, dents, deformation, distortion or missing parts.

5. Shoulder Adjustment Buckle			
6. Leg & Waist Buckles			
7. D-Rings (Dorsal, Side or Shoulder)			

WEBBING
Webbing should not show any kinks, knots, broken strands, cuts, burns, corrosion, welding splatter, paint coating or excessive abrasion.

8. Shoulder Straps			
9. Chest Straps			
10. Leg Straps			
11. Back Straps			

STITCHING
Pulled or cut stitches may be an indication the harness has been impact loaded.

12. Shoulder, Chest, Leg & Back Stitches			
--	--	--	--

NOTES:

HARNES CONFIGURATION:

	Pass Thru	Quick Connect	Tongue
CHEST STRAPS			
LEG STRAPS			

INSPECTION POINTS

